



COMMERCIAL KITCHEN EQUIPMENTS



PRODUCT
CATALOUGE

2025

Two Burner Indian Cooking Range



Use:

Used for cooking first, second & third course dishes in the cookware.

Specification:

- Made of Stainless Steel AISI-304 included angle framework
- Operate LPG/PNG Gas as per requirement
- Individual control & Pilot Knob
- Heavy duty top cast iron
- Removable Type Drip Tray

Item Code	Dimension	Burner	CI Grill
RDE-H02-A	48"x24"x34+4"	G-10, 70000 BTU/Hr 1.6 Kg. Gas Cons/Hr	16"x16"
RDE-H02-B	48"x24"x34+4"	G-9, 40000 BTU/Hr 0.9 Kg. Gas Cons/Hr	14"x14"

Three Burner Indian Cooking Range



Use:

Used for cooking first, second & third course dishes in the cookware.

Specification:

- Made of Stainless Steel AISI-304 included angle framework
- Operate LPG/PNG Gas as per requirement
- Individual control & Pilot Knob
- Heavy duty top cast iron
- Removable Type Drip Tray

Item Code	Dimension	Burner	CI Grill
RDE-H03-A	72"x24"x34+4"	G-10, 70000 BTU/Hr 1.6 Kg. Gas Cons/Hr	16"x16"
RDE-H03-B	60"x24"x34+4"	G-9, 40000 BTU/Hr 0.9 Kg. Gas Cons/Hr	14"x14"

Dosa / Hot Plate



Use:

Used for cooking Dosa, Uttapam, Paratha & Pancakes due to the direct contact of the food with the frying surface in the cookware.

Specification:

- Made of Stainless Steel AISI-304 included angle framework
- Operate LPG/PNG Gas as per requirement
- 12 Nos. RV Burner & 1 Nos. Pilot Burner
- 15 mm Thick Polished MS Cooktop
- At the front panel there is a collector Oil tray

Item Code	Dimension	Burner	CI Grill
RDE-H05-A	48"x30"x34+4"	V-900, 70000 BTU/Hr. 1.58 Kg. Gas Cons/Hr. each	44"x23"
RDE-H05-B	42"x30"x34+4"	V-750, 70000 BTU/Hr. 1.58 Kg. Gas Cons/Hr. each	38"x23"
RDE-H05-C	36"x30"x34+4"	V-600, 70000 BTU/Hr. 1.58 Kg. Gas Cons/Hr. each	32"x23"



Trolley



Heating Trolley



Service Trolley



Sink

Two Burner Combi Range



Use:

Used for all types of cooking-stir frying, deep frying, stewing, braising, boiling Chinese soup & noodles in the cookware

Specification:

- ◆ Made of Stainless Steel AISI-304 included angle frame
- ◆ Operate LPG/PNG Gas as per requirement
- ◆ Individual Control & Pilot Knob
- ◆ With 1 Nos. High Pressure (T35) & 1 Nos. Indian (G10) Burner
- ◆ Perforated 1" Dia S.S. pipe with 3 mm Dia Holes for water spray at front
- ◆ Individual Control & Pilot Knob
- ◆ 1 Nos. 400 mm long gooseneck type of Swivel faucet mounting on back splash

Item Code	Dimension	Burner	CI Grill
RDE-H10	48"x30"x34"+12"	T-35, 70000 BTU/Hr 1.58 Kg. Gas Cons/Hr G-10, 70000 BTU/Hr 1.58 Kg. Gas Cons/Hr	15" Dia Dome 14"x14"

Single Burner Chiness Range



Use:

Used for all types of cooking-stir frying, deep frying, stewing, braising, boiling Chinese soup & noodles in the cookware

Specification:

- ◆ Made of Stainless Steel AISI-304 included angle frame
- ◆ Operate LPG/PNG Gas as per requirement
- ◆ Individual control & Pilot Knob
- ◆ With 2 Nos. High Pressure (T35)
- ◆ Individual Control & Pilot Knob

Item Code	Dimension	Burner	CI Grill
RDE-H11	24"x30"x34+12"	T-35, 70000 BTU/Hr 1.58 Kg. Gas Cons/Hr	15" Dia Dome

Twin Tank Deep Fat Fryer



Use:

Used for cooking many fast foods like, potatoes & other culinary & confectionary product, and making crisp at canteen, School Mess & Hotel Mess in the cookware

Specification:

- ◆ Made of Stainless Steel included angle framework with auto Timer & temperature controller
- ◆ It has two Tanks with 8 Ltr. Oil capacities with bottom drain wall
- ◆ Temperature can be smoothly controlled within the range +20 + 190

Item Code	Dimension	Specification
RDE-H012-A	28"x30"x34+4"	Twin Tank 8 Ltr, Each tank cap.
RDE-H012-B	16"x30"x34+4"	Single Tank 8 Ltr, cap.

Tilting Type Bulk Cooker



Use:

Boiling of water, Rice, Pulse & Potato Etc. for bulk cooking at Industrial Canteens, Government or Military Messes & Mid-Day meals,

Specification:

- ◆ Made of Stainless Steel included angle framework
- ◆ Operate LPG/PNG Gas as per requirement
- ◆ Individual Control & Pilot Knob
- ◆ Heavy Duty Valve Fitted at bottom of vessel for draining water or cooked material

Item Code	Dimension	Capacity	Burner
RDE-BH04-A	36"x30"x42"	80 Ltrs	G-10, 70000 BTU/Hr 3.5 Kg. Gas Cons/Hr
RDE-BH04-B	42"x36"x48"	120 Ltrs	G-11, 10000 BTU/Hr 2.2 Kg. Gas Cons/Hr
RDE-BH04-C	48"x36"x48"	160 Ltrs	G-11, 10000 BTU/Hr 2.2 Kg. Gas Cons/Hr

Tilting Type Brat Pan



Use:

Used to fry products saute vegetable, braising, searing, shallow frying and general cooking at industrial Canteens, Government or Military & Mid-Day meals

Specification:

- ◆ Made of Stainless Steel included angle framework
- ◆ Operate LPG/PNG Gas as per requirement
- ◆ Individual control & Pilot Knob
- ◆ The pan is equipped with a mechanism of lifting & lowering what provide convenient leaning & Service of the pan

Item Code	Dimension	Capacity	Burner
RDE-BH04-A	36"x30"x42"	80 Ltrs	G-10, 70000 BTU/Hr 3.5 Kg. Gas Cons/Hr
RDE-BH04-B	42"x36"x48"	120 Ltrs	G-11, 10000 BTU/Hr 2.2 Kg. Gas Cons/Hr
RDE-BH04-C	48"x36"x48"	160 Ltrs	G-11, 10000 BTU/Hr 2.2 Kg. Gas Cons/Hr

Masala Trolley



Use:

Keep vivid type of spices or masala in a fresh and hygienic way in commercial Kitchen

Specification:

- ◆ Made of Stainless Steel
- ◆ 12 Nos. Stainless 1/6* 150 Deep GN Pan with Lid
- ◆ 1 Nos. S.S. Handle
- ◆ 4 Nos. 5" Diameter heavy duty rubber tired Swivel type caster-two with brake

Item Code	Dimension
RDE-H012	32"x24"x34"

Tea Snacks Service Trolley



Use:

Used for Serving Tea Snacks for industrial canteens, hospitals & Plants

Specification:

- ◆ Made of Stainless Steel
- ◆ 4 Nos. (1/1)*150 Deep GN Pan with Lid for Keeping Snacks
- ◆ 2 Nos. 21"x19"x4" Tray for Tea Cup
- ◆ 6 Nos. 6"x5"x6" Pockets for Keeping Napkin on side
- ◆ 1 Nos. 20"x8"x15" folding Type Dustbin
- ◆ 4 Nos. 5" Diameter heavy duty rubber tired Swivel type caster - two with brake

Item Code	Dimension
RDE-BH06	5"+41"+8"x22"x36"+4"

Hot Basin Marie



Use:

Short - term Keeping hot of the first & second courses in gastronorm containers & their serving to customers

Specification:

- ◆ Made of Stainless Steel
- ◆ 5 Nos. (1/1)*150 mm Deep GN pan with Lid
- ◆ The smooth temperature regulation is provided from +30 to 85°C
- ◆ The guiding rails with drip tray for supporting delivered service
- ◆ 1 Nos. 2 KW S.S. tubing heating element & element clamped 25 mm off bottom of tank
- ◆ Control panel complete with ON/Off switch, indicator light & Adjustable Thermostat

Item Code	Dimension
00000000	72"x27"+12x34"

Electric Plate Warmer



Use:

Keep dishes primed ready for use with this range of plate warmers, designed to achieve and maintain optimum temperatures. Safely heating and holding plates, professional service and optimum results are guaranteed. Serving food on warm plates will Keep dishes at their best for longer periods than if served on cold crockery, ensuring an overall better dining experience for guests.

Item Code	Dimension	Capacity	
RDE-BH08-A	18"x36"x30"	50x2 Plate = 100 Plate	Double Holder Cart
RDE-BH08-B	18"x19"x30"	50x1 Plate = 50 Plate	Single Holder Cart

Dough Kneading Machine



Use:

Used for Mixing flour/Aata in Restaurant Kitchen, Industrial canteen.

Specification:

- Bowl & Kneading Shaft made of stainless steel
- Rugged MS Construction - Painted.
- Powerful gear driven
- Robust durable design

Model	RDP01 -A	RDP01 -B	RDP01 -C	RDP01 -D
Capacity Kgs.	10	15	20	30
Motor HP (KW)	1.0 (0.75 kw)	1.0 (0.75 kw)	1.5	1.5
Voltage	230V	230V	230/440V	440V

Pulveriser



Use:

Used for Grinding wet pulses, red chillies, turmeric & black paper & Gravy etc

Specification:

- Made of Stainless Steel Body
- Five numbers of different size holes screen for getting different mesh powders.
- Robust durable design

Model	RDP01 -A	RDP01 -B	RDP01 -C	RDP01 -D
Motor HP (KW)	1 HP (0.75 Kw)	2 HP (1.5 Kw)	3 HP (2.2 Kw)	5 HP (3.8 Kw)
Capacity Kgs.	10/15 Kgs/Hrs.	30/35 Kgs/Hrs.	55/66 Kgs/Hrs.	75/80 Kgs/Hrs.
Voltage	230V	230V	230/440V	440V

Wet Masala Grinder



Use:

Grinders are used widely used for grinding various Indian spices & Rava for Dosa

Specification:

- Bowl made of stainless steel
- Detachable Cylindrical Granite Roller Stone Assembly Powerful gear driven
- The Granite Roller Stone Assembly is fitted with two Wipers to ensure 100% grinding in quicker time

Model	RDP03 -A	RDP03 -B	RDP03 -C
Capacity Kgs.	7	10	15
Motor HP	1.0	1.0	1.5
Voltage	230V	230V	230/440V

Tilting Wet Masala Grinder



Use:

Grinders are used widely used for grinding various Indian spices & Rava for Dosa,

Specification:

- The Drum, Motor housing, Frames are made of High-Quality Stainless Steel
- Detachable Cylindrical Granite Roller Stone Assembly.
- Unique adjustable Load Balancing System provided for even spread of load and for very efficient grinding
- Tilting system enables the drum to tilt and lock at 100 degrees for easier and hygienic transfer of batter

Model	RDP04 -A	RDP04 -B	RDP04 -C	RDP04 -D
Capacity Kgs.	7	10	15	25
Motor HP	1.0	1.0	1.5	3.0
Voltage	230V	230V	230/440V	440V

Potato Peeler



Use:

Used for peeling potato & other edible roots at Restaurant Kitchen, Industrial canteen.

Specification:

- The body of machine made of stainless steel
- Strong emery bonding for peeling
- Operations with running water supply
- Drain outlet provided for waste disposal

Model	RDP05 -A	RDP05 -B
Capacity Kgs.	10	20
Motor HP (KW)	0.5 (0.4 Kw)	1.0 (0.75 Kw)
Voltage	230V	230V

Vegetable Cutting Machine



Use:

Used for cutting & slicing fresh & cooked vegetables & fruits at Restaurant Kitchen, Industrial canteen & public catering.

Specification:

- The body of machine made of stainless steel
- Comprehensive range of 7 discs for slicing, ripple cutting, grating and cutting into sticks, strips or with optimum.
- High-speed electric motor for continuous cuttings
- Robust durable design

Model	RDP01 -A
Capacity Kgs.	200-250 Kg/Hr
Motor HP	1.0 (0.75 Kw)
Voltage	230V

Meat Mincer (Electric)



Use:

Used for mincing meat & fish stuffing sausages at Restaurant Kitchen, catering enterprises.

Specification:

- All the components are made of stainless Steel
- The Hopper diameter is 40 mm
- The standard delivery set includes a screw, a grater plate, two blades, a plate 9 mm & a plate 5 mm
- Robust durable design

Model	RDP07
Capacity Kgs.	200-250 Kgs./Hr
Motor HP	1.0 (0.75 Kw)
Voltage	230V

Spiral Dough Mixer



Use:

Used for mixing both light & dough Kneading at bakeries & public catering enterprises.

Specification:

- The spiral, the bowl & the dough breaker are made of stainless steel
- White painted steel structure.
- Powerful gear driven
- Available manual control & digital control model

Model	RDP08 -A	RDP08 -B	RDP08 -C
Bowl Cap Ltr.	28 (1 Speed)	45 (2 Speed)	66 (2 Speed)
Motor (KW)	1.7 Kw	2.0 Kw	3.5 Kw
Voltage	230V	440V-3 P	440V-3 P

Planetary/Bakery Mixture



Use:

A planetary mixer is industrial mixing equipment used to prepare food, chemical, ceramic dough or other types of products, replacing manual labour through a mechanical system that allows us to produce continuously large quantities of dough

Specification:

- Bowl made of stainless Steel
- Detachable Cylindrical Granite Roller stone Assembly
- Powerful gear driven
- The Granite Roller Stone Assembly is fitted with two Wipers to ensure 100% grinding in quicker time

Model	RDP03 -A	RDP03 -B	RDP03 -C	RDP03 -C	RDP03 -C	RDP03 -C
Bowl Cap Ltr.	7.5	10	20	28	38	60
Motor (KW)	0.32 Kw	0.6	1.1	1.5	1.5	2.2
Voltage	230V	230V	230V	230V	230V	440v-3p

Single Deck Oven



Use:-

Used for baking confectionery & bakery products like Biscuit, Chips, Doughnut, Cakes and Breads at public catering enterprises.

GAS OPERATED:-

Model	Capacity	Wattage (W)	Voltage	Thermal Load MJ/Hr	Dimension	No. of Baking Tray
RDP10-A	10 Kg/Hr,	48	230V-1P	40 MJ/Hr 0.9Kg Gas/Hr.	40"x29"x22"	1
RDP10-B	20 Kg/Hr,	60	230V-1P	60 MJ/Hr 1.2Kg Gas/Hr.	53"x36"x26"	2

ELECTRIC OPERATED:-

Model	Capacity	Wattage (W)	Voltage	Dimension	No. of Baking Tray
RDP10-C	20 Kg/Hr,	6600	230V-1P	50"x34"x24"	2

Double Deck Oven



Use:-

Used for baking confectionery & bakery products like Biscuit, Chips, Doughnut, Cakes and Breads at public catering enterprises.

ELECTRIC OPERATED:-

Model	Capacity	Wattage (W)	Voltage	Dimension	No. of Baking Tray
RDP11-B	40 Kg/Hr,	13200	440V-3P	50"x34"x48"	4

Three Deck Oven



Use:-

Used for baking confectionery & bakery products like Biscuit, Chips, Doughnut, Cakes and Breads at public catering enterprises.

GAS OPERATED:-

Model	Capacity	Wattage (W)	Voltage	Thermal Load MJ/Hr	Dimension	No. of Baking Tray
RDP12-A	60 Kg/Hr,	180	230V-1P	180 MJ/Hr 3.6Kg Gas/Hr.	53"x36"x72"	6
RDP12-B	90 Kg/Hr,	210	230V-1P	210 MJ/Hr 14.2Kg Gas/Hr.	70"x36"x26"	9

ELECTRIC OPERATED:-

Model	Capacity	Wattage (W)	Voltage	Dimension	No. of Baking Tray
RDP12-C	60 Kg/Hr,	19800	440V-3P	50"x34"x64"	6
RDP12-D	90 Kg/Hr,	25200	440V-3P	66"x34"x65"	7

Heavy Duty Industrial Mixer



Use:

Used for special gravy of all type of vegetable, wet & Dry grinding of grain & nut grinding at public catering enterprises.

Specification:

- Body made of Stainless Steel
- Easy to Clean
- Robust durable design

Model	RDPO7	RDPO7
Bowl Cap Ltr.	3.0	5.0
Motor HP (KW)	1.0 HP (0.75 Kw)	1.5 HP (1.0 Kw)
Voltage	230V	230V

Dough Sheeter



RDP14	
Conveyer Belt (wide in mm)	500
Conveyer Belt (Length in mm)	2000
Voltage / Phase (V/Ph)	380-415/3
Frequency (Hz)	50
Wattage (W)	400
Dimension	2540 x 910 x 1150
Weight (Kg)	235

Ice Crusher



Use:

This electric ice crusher is great to make troublesome big ice cubes into snow cone at ease.

Specification:

- The upgraded groove fits both tray and cup to contain shaved ices, more practical.
- With a drain pipe to avoid a wet working environment after use.
- It adopts double shaving blades, which greatly increased the crush efficiency and meets the demand of commercial use.
- The handle is covered with insulated rubber to ensure safe and non-slip operation.

RDP15	
Dimension	425 x 205 x 320mm
Hoper Dimeter	108 mm
Motor Speed	1400 RPM
Power Consumption	180 W

Pot Rack



Item Code	Unit Size	No. of Shelves
RDW7-A	48"x24"x66" / 72"	3, 4
RDW7-B	54"x24"x66" / 72"	3, 4
RDW7-C	60"x24"x66" / 72"	3, 4

Wall Shelf



Item Code	Unit Size
RDW8-A	48" x 12"
RDW8-B	54" x 12"
RDW8-C	60" x 12"
RDW8-D	66" x 12"
RDW8-E	72" x 12"

L Type Dishlanding Table with Sink:- (RDW9)



Use:

Hand shower for preliminary rinsing of dirty cutlery before loading it into a dishwasher

Specification:

- 1 Nos. seamless sink of 450 x 450 x 300mm
- 2 Nos. Waste Hole
- 1 Nos. Over Tray Rack

Dimension:

1950+2550x900x850+550

Double Glass Door Refrigerator (RDE-1250G)



Specification:

- 60 mm thick polyurethane insulation for better energy efficiency.
- Stainless steel AISI 304 internal & external panels including back panel.
- Large storage area suitable to contain 2/1 GN pan & 6 Nos. adjustable S.S. wire mesh shelves.
- Refrigerated models have operating temperature that can be adjusted -2 to 10° C.
- Self Closing Doors with magnetic Gasket.
- Auto defrosting and auto evaporation of condensation water.
- Digital controller allows for temperature & parameter setting.
- Digital controller allows for temperature of + 43° C.
- Forced air circulation for rapid cooling & an even temperature distribution.

Technical Specification:

- Supply Voltage: - 230 V/1 ph/50Hz (475 Watts)
- Ltr. Capacity: - 600 Ltr.
- External Dimension: - 721 x 800 x 2100 mm
- Refrigerant Type: - R134a(300 g)
- Operating Temp Min.: -2° C.
- Operating Temp Max.: 10° C.
- Operating Mode: Ventilated
- Cooling Unit: Inbuilt
- Defrost Type: Electric

Single Glass Door Refrigerator (RDE-600G)



Specification:

- 60 mm thick polyurethane insulation for better energy efficiency.
- Stainless steel AISI 304 internal & external panels including back panel.
- Large storage area suitable to contain 2/1 GN pan & 6 Nos. adjustable S.S. wire mesh shelves.
- Refrigerated models have operating temperature that can be adjusted -2 to 10° C.
- Self Closing Doors with magnetic Gasket.
- Auto defrosting and auto evaporation of condensation water.
- Digital controller allows for temperature & parameter setting.
- Performance at ambient temperature of + 43° C.
- Forced air circulation for rapid cooling & an even temperature distribution.

Technical Specification:

- Supply Voltage: - 230 V/1 ph/50Hz (475 Watts)
- Ltr. Capacity: - 600 Ltr.
- External Dimension: - 721 x 800 x 2100 mm
- Refrigerant Type: - R134a(300 g)
- Operating Temp Min.: -2° C.
- Operating Temp Max.: 10° C.
- Operating Mode: Ventilated
- Cooling Unit: Inbuilt
- Defrost Type: Electric

Pick Up Table with RR System



Item Code	Unit Size
RWT4-A	36"x24"x34" + 4"
RDW4-B	48"x24"x34" + 4"
RDW4-C	60"x24"x34" + 4"
RDW4-D	72"x24"x34" + 4"

Three Side Covering Table with 2 U.S.



Item Code	Unit Size
RWT5-A	36"x24"x34" + 4"
RDW5-B	48"x24"x34" + 4"
RDW5-C	60"x24"x34" + 4"
RDW5-D	72"x24"x34" + 4"

Work Table with Sink



Item Code	Unit Size	No. of U.S.
RWT6-A	36"x24"x34" + 4"	1
RDW6-B	48"x24"x34" + 4"	1
RDW6-C	60"x24"x34" + 4"	2
RDW6-D	72"x24"x34" + 4"	2

Platform Trolley



Item Code	Burner
RWT10	36"x24"x36"

Mobile Tray Set Up Rack & GN Pan Trolley



Item Code	Unit Size	No. of U.S.
RDW3-B	20"x27"x72"	19 Tray

Water Cooler



Specification:

- ◆ Elegant design for Restaurant, School, Canteen etc.
- ◆ Stainless steel AISI 304 Internal & external body
- ◆ 50 mm thick polyurethane insulation for better energy efficiency
- ◆ Independent on/off compressor switch
- ◆ Static cooling technology with thermostat

Item Code	Dimension	Cooling Capacity	Storage Capacity	Power Consum.
RDE-004-40/80	22"x22"x48"	40 Ltr.	80 Ltr.	430 W
RDE-004-60/120	24"x24"x56"	60 Ltr.	120 Ltr.	680 W
RDE-004-150/150	24"x24"x60"	150 Ltr.	150 Ltr.	1300 W
RDE-004-200/250	28"x28"x65"	200 Ltr.	250 Ltr.	1900 W
RDE-004-300/300	32"x32"x65"	300 Ltr.	300 Ltr.	2100 W

COMMERCIAL KITCHEN EQUIPMENT



One Stop Commercial
Kitchen Solution



Plot No.127, Sec-53, Phase-II, HSIIDC, Industrial Estate, Kundli Sonepat Haryana-131028, India



9811017907, 9811735500



Sales.laserform127@gmail.com



www.laserform.in